

LG DL系列常用水泵规格、型号、参数一览表

附表 1 .

水泵型号	流量 m ³ / h	扬程 m	电机功率 kW	水泵型号	流量 m ³ / h	扬程 m	电机功率 kW
25LG3-10x3	3	30	1.1	80LG50-20x2	50	40	11
25LG3-10x4		40	1.5	80LG50-20x3		60	15
25LG3-10x5		50	1.5	80LG50-20x4		80	18.5
25LG3-10x6		60	2.2	80LG50-20x5		100	22
25LG3-10x7		70	2.2	80LG50-20x6		120	30
32LG6.5-15x2	6.5	30	1.5	65DL32-15x2	32	30	5.5
32LG6.5-15x3		45	2.2	65DL32-15x3		45	7.5
32LG6.5-15x4		60	3	65DL32-15x4		60	11
32LG6.5-15x5		75	4	65DL32-15x5		75	15
32LG6.5-15x6		90	5.5	65DL32-15x6		90	15
40LG12-15x2	12	30	2.2	80DL50-20x2	50	40	11
40LG12-15x3		45	3	80DL50-20x3		60	15
40LG12-15x4		60	4	80DL50-20x4		80	22
40LG12-15x5		75	5.5	80DL50-20x5		100	30
40LG12-15x6		90	7.5	80DL50-20x6		120	30
50LG24-20x2	24	40	5.5	100DL100-20x2	100	40	18.5
50LG24-20x3		60	7.5	100DL100-20x3		60	30
50LG24-20x4		80	11	100DL100-20x4		80	37
50LG24-20x5		100	11	100DL100-20x5		100	45
50LG24-20x6		120	15	100DL100-20x6		120	55
65LG36-20x2		40	7.5	150DL160-25x2		50	37
65LG36-20x3		60	11	150DL160-25x3		75	55
65LG36-20x4		80	15	150DL160-25x4		90	75
65LG36-20x5		100	18.5	150DL160-25x5		125	90

65LG36- 20x6	36	120	22	150DL160- 25x6	160	150	110
-----------------	----	-----	----	-------------------	-----	-----	-----

IS系列常用水泵规格、型号、参数一览表

附表 2

水泵型号	流量 m ³ / h	扬程 m	电机功率 kW	水泵型号	流量 m ³ / h	扬程 m	电机功率 kW
IS50-32-125	12.5	20	2.2	IS100-65-315	100	125	75
IS50-32-160	12.5	32	3	IS100-65-315A	95	114	55
IS50-32-200	12.5	50	5.5	IS100-65-315B	90	103	55
IS50-32-250	12.5	80	11	IS125-100-200	200	50	45
IS65-50-125	25	20	3	IS125-100-200A	187	44	37
IS65-50-160	25	32	5.5	IS125-100-200B	173	38	30
IS65-40-200	25	50	7.5	IS125-100-250	200	80	75
IS65-40-250	25	80	15	IS125-100-250A	187	70	55
IS65-40-315	25	125	30	IS125-100-250B	173	60	45
IS80-65-125	50	20	5.5	IS125-100-315	200	125	110
IS80-65-160	50	32	7.5	IS125-100-315A	191	73	110
IS80-65-160A	46	28	7.5	IS125-100-315B	181	71	90
IS80-65-160B	43	24	5.5	IS125-100-400	100	50	30
IS80-50-200	50	50	15	IS125-100-400A	93	44	22
IS80-50-200A	46	44	11	IS125-100-400B	86	38	18.5
IS80-50-200B	43	38	11	IS150-125-250	200	20	18.5
IS80-50-250	50	80	22	IS150-125-250A	187	17.5	15
IS80-50-250A	46	70	18.5	IS150-125-250B	173	15	11
IS80-50-250B	43	60	15	IS150-125-315	200	32	30
IS80-50-315	50	125	37	IS150-125-315A	187	28	22
IS80-50-315A	47	114	37	IS150-125-315B	173	24	18.5
IS80-50-315B	45	103	30	IS150-125-400	200	50	45
IS100-80-125	100	20	11	IS150-125-400A	187	44	37
IS100-80-125A	89	16	7.5	IS150-125-400B	173	38	30

IS100-80-160	100	32	15	IS200-150-250	400	20	37
IS100-80-160A	93	28	11	IS200-150-250A	374	17.5	30
IS100-80-160B	86	24	11	IS200-150-250B	346	15	22
IS100-65-200	100	50	22	IS200-150-315	400	32	55
IS100-65-200A	93	44	18.5	IS200-150-315A	374	28	45
IS100-65-200B	86	38	15	IS200-150-315B	346	24	37
IS100-65-250	100	80	37	IS200-150-400	400	50	90
IS100-65-250A	93	70	30	IS200-150-400A	374	44	75
IS100-65-250B	86	60	30	IS200-150-400B	346	38	55

SH系列常用水泵规格、型号、参数一览表

附表 3

水泵型号	流量 m ³ / h	扬程 m	电机功率 kW	水泵型号	流量 m ³ / h	扬程 m	电机功率 kW
6sh-6	162	78	55	12sh-9	792	58	190
6sh-6A	144	62	45	12sh-9A	720	49	160
6sh-9	170	47	37	12sh-9B	684	43	132
6sh-9A	144	40	30	12sh-13	792	32	110
8sh-6	234	93	110	12sh-13A	720	26	75
8sh-6A	224	83	90	12sh-19	792	19	75
8sh-9	288	62	75	12sh-19A	720	16	55
8sh-9A	270	47	55	14sh-9A	1170	65	300
8sh-13	288	41	55	14sh-9B	1080	55	260
8sh-13A	270	36	37	14sh-13	1260	42	230
10sh-6	286	65	132	14sh-13A	1116	37	160
10sh-6A	468	54	110	14sh-19	1260	26	132
10sh-9	486	38	75	14sh-19A	1116	21	90
10sh-9A	468	30	75	20sh-13	2016	35	310
10sh-13	486	23	55	20sh-13A	1870	31	310
10sh-13A	414	20	37	20sh-19	2016	22	185
12sh-6	792	90	300	20sh-19A	1870	17	132
12sh-6A	756	78	260	24sh-19A	2880	27	310
12sh-6B	720	67	230	24sh-28	2880	21	250

注：上述水泵参数系山东双轮集团有限公司部分产品参数，若选择其它水泵，请提供有关水泵、电机参数。